

## 2022+ Model FastCOLOUR Printer Default Settings

Setting	F1-1800 1800mm <b>Single</b> Head	F1-1800D 1800mm <b>Double</b> Head
<b>Factory Settings</b>		
Station	Lift	
Wiper	Pop, Lift	
Printing Width	195cm	190cm
Raster Type	B	
Cart Motor	DC	Servo
Paper Motor	Step	
Wiper Direction	Normal	
Paper Direction	Reverse	
Car Direction	Cannot Change. If Cart Move Wrong Direction, Swap Wires	
Acc Distance	80mm	
Paper Speed	50	
LCD Type	B	
UV Type	D	
Auto Clean	Spit: Printhead Flush Ink Only Clean: Full Cleaning Sequence	
Wiper Speed	Between 60 to 70	
Station Speed	84	
Do Wipe Speed	2	
Fan in Mode	可控 (Adjustable in Menu) 常开 (Always On)	

Head Width	50mm (for XP600 Printhead)		
Dry Set	Dry: For UV Printer, Control LED Lamps Heat: For Solvent/Sublimation etc (P.S Still need to adjust wires)		
<b>Advance Setup</b>	<i>(Password Protected)</i>		
Voltage Adjust	560		
Voltage Type	S 097f0600		
Colour	CYCcMm		
Colour Dual Seq.		KKCCMMYYCCMM	
Print Empty	Not Print Empty Pass		
Print more	0		
Spit Switch	Close		
Spit Dots	10		
Spit Empty Data	3		
Chang config	All Colour		
White Repeat		1 Pass (Increase Passed for Density)	
<b>UV Lamp Control</b>	<b>Left LED</b>	<b>Both LEDs (Left &amp; Right)</b>	
R to L On	1800		3600
R to L Off	8000		8500
L to R On	3600		3600
L to R Off	-1800		0
Distance	5200		9500