

GRAPHTEC

2019

Supplies & Accessories

www.graphteccorp.com

Graphtec Supplies & Accessories

Cutting plotter









- 1. Cutting blade
 - 2. Cutting blade holder
 - 3. Cutting mat
 - 4. Protect sheet
 - 5. Adsorption mat
 - 6. Cross cutter
 - 7. Pouncing tool
 - 8. Creasing / Scoring tool
 - 9. Loupe
 - 10. Water-based fiber-tip pen
 - 11. Water-based fiber-tip pen holder
 - 12. Oil-based ballpoint pen
 - 13. Oil-based ballpoint pen holder
 - 14. Pen adapter
-

Cutting protter

Supported product CE5000 / CE6000Plus / CE6000 / CE8000/ CE8600 / CE LITE-50 / FC4500 / FC2250 / FCX2000 / FCX4000

Published item 1. Cutting blade 2. Cutting blade holder 3. Blade type and typical application 4. Blade and the corresponding holder List
5. Cutting mat 6. Protect sheet 7. Adsorption mat 8. Cross cutter blade 9. Pouncing tool 10. Creasing / Scoring tool
11. Loupe 12. Water-based fiber-tip pen 13. Water-based fiber-tip pen holder 14. Oil-based ballpoint pen
15. Oil-based ballpoint pen holder 16. Pen adapter

■ 1. Cutting blade














Item	Model No.	Discription	Package	Supported product								
				Grit rolling type				Flatbed type				
				CE5000	CE6000Plus	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000
	CB09UB-5	0.9 mm diameter. Angle 45°, Supersteel Self-adhesive marking film (vinyl, fluorescent, refractive), thin sheet, up to 0.25 mm thick.	5 blades/pack	●	●	●	●		●	●	●	●
	CB09UB-K60-5	0.9 mm diameter. Angle 60°, Supersteel Thinner film (Tint film), 0.03 mm to 0.25 mm thick.	5 blades/pack		●	●	●					
	CB15U-5	1.5 mm diameter. Angle 45°, Supersteel Rigid or thick film or sheet, heavy paper (pattern paper, oil board), 0.25 mm to 0.5 mm thick.	5 blades/pack	●	●	●	●		●	●	●	●
	CB15UA-5	1.5 mm diameter. Angle 45°, Supersteel High-intensity reflective film or harder film, up to 0.5 mm thick.	5 blades/pack			●	●		●	●	●	●
	CB15UA-K30-5	1.5 mm diameter. Angle 30°, Supersteel Rigid or thick sheet, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25 mm thick).	5 blades/pack			●	●		●	●	●	●
	CB15U-K20-2SP	1.5 mm diameter. Angle 20°, Supersteel Sandblast resist rubber, up to 1.0 mm thick.	2 blades/pack			●	●		●	●	●	●
	CB15U-K30-5	1.5 mm diameter. Angle 30°, Supersteel Rigid or thick sheet, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25 mm thick).	5 blades/pack			●	●		●	●	●	●
	CB30UC-1	3.0 mm diameter. Angle 45°, Supersteel Rigid or thicker sheet (cardboard E flute), up to 1.5 mm thick.	1 blade/pack							●		

3. Blade type and typical application



















We offer several high-quality blade for each material so that it can be used in a variety of applications.

○ : Attached as standard accessory(the quantity attached is different)

● : Available

			Compatible models			
			Grit rolling type		Flatbed type	
Item	Specification	Suitable media type	FC8600 Series	CE6000Plus / CE6000 Series	FCX2000 Series	FCX4000/ FC4550 Series
 CB09UA-5 * Spring attached.	[Spring] Yes [Material] Super Steel [Diameter] φ0.9mm [Angle] 45°	Self-adhesive marking film (vinyl, fluorescent, reflective), Paper, Heat transfer media [Thickness] up to 0.25mm	●	●	●	●
 CB09UB-5	[Spring] No [Material] Super Steel [Diameter] φ0.9mm [Angle] 45°		○	○	●	●
 CB09UA-K60-5 * Spring attached.	[Spring] Yes [Material] Super Steel [Diameter] φ0.9mm [Angle] 60°	Special blade for cutting the window tint film or thin film [Thickness] up to 0.25mm	●	●		
 CB09UB-K60-5	[Spring] No [Material] Super Steel [Diameter] φ0.9mm [Angle] 60°		●	●		
 CB15U-5SP * Spring attached.	[Spring] Yes [Material] Super Steel [Diameter] φ1.5mm [Angle] 45°	Heavy paper/board [Thickness] up to 0.5mm	●	●	●	●
 CB15U-5	[Spring] No [Material] Super Steel [Diameter] φ1.5mm [Angle] 45°	Heavy paper/board [Thickness] up to 0.5mm Heavy paper/board (pattern paper, oil board) [Thickness] up to 0.5mm	●	●	○	○
 CB15U-K30-5SP * Spring attached.	[Spring] Yes [Material] Super Steel [Diameter] φ1.5mm [Angle] 30°	Heavy paper/board Corrugated board (F,G flute) Foam sheet, Magnet sheet, Rubber sheet for Sandblast [Thickness] up to 1.1mm For cutting small detailed characters(less than 10mm) Self-adhesive marking film (vinyl, fluorescent, reflective) [Thickness] up to 0.25mm	●	●	●	●
 CB15U-K30-5	[Spring] No [Material] Super Steel [Diameter] φ1.5mm [Angle] 30°	Heavy paper/board Corrugated board (F,G flute) Foam sheet, Magnet sheet, Rubber sheet for Sandblast [Thickness] up to 1.1mm For cutting small detailed characters(less than 10mm) Self-adhesive marking film (vinyl, fluorescent, reflective) [Thickness] up to 0.25mm	●	●	○	●
 CB15U-K20-2SP	[Spring] Yes [Material] Super Steel [Diameter] φ1.5mm [Angle] 20°	Rubber sheet for Sandblast [Thickness] up to 1.0mm			●	●
 CB15UA-5	[Spring] No [Material] Super Steel [Diameter] φ1.5mm [Angle] 45°	High intensity reflective film [Thickness] up to 0.5mm	●		●	●
 CB15UA-K30-5	[Spring] No [Material] Super Steel [Diameter] φ1.5mm [Angle] 30°	High intensity reflective film [Thickness] up to 1.0mm	●		●	●
 CB30UC-1	[Spring] Yes [Material] Super Steel [Diameter] φ3.0mm [Angle] 45°	Corrugated board (E,F,G flute) [Thickness] up to 1.5mm * Cutting accuracy is not guaranteed. Be sure to try it before using it.			●	
 PM-CB-001	[Spring] Yes [Material] Super Steel [Diameter] φ3.0mm [Angle] 30°	General purpose rubber sheet (Durometer:60 to 65) [Thickness] 1.0 ~ 2.0mm * Cutting accuracy is not guaranteed. Be sure to try it before using it.			●	


■ 4. Blade and the corresponding holder List

		corresponding holder				
		PHP33- CB09N-HS Spring built-in type	PHP35- CB09-HS Spring built-in type	PHP33- CB15N-HS Spring built-in type	PHP35- CB15-HS Spring built-in type	PM-CH-001
Blade						
Diameter	Item					
φ0.9mm	 CB09UA-5	●	●			
	 CB09UB-5	●	●			
φ1.5mm (*1)	 CB09UA-K60-5	●	●			
	 CB09UB-K60-5	●	●			
	 CB15U-5SP			●	●	
	 CB15U-5			●	●	
	 CB15U-K30-5SP			●	●	
φ1.5mm (*1)	 CB15U-K30-5			●	●	
	 CB15U-K20-2SP			●	●	
	 CB15U A-5			●	●	
φ3.0mm (*2)	 CB15UA-K30-5			●	●	
	 CB30UC-1					●
φ3.0mm (*2)	 PM-CB-001					●

(*1) It is required to remove the spring.

(*2) Cutting accuracy is not guaranteed. Be sure to try it before using it.

■ 5. Cutting mat

Item	Model No.	Discription	Package	Supported product									
				Grit rolling type				Flatbed type					
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000	
	CE6-CM120-2	For CE6000-120 /PLUS	2 mats/pack		●								
	CE6-CM60-2	For CE6000-60 /PLUS	2 mats/pack		●								
	CE6-CM40-2	For CE6000-40 /PLUS	2 mats/pack		●								
	PM-CR-001	For replacing cutting mat in CE LITE-50	1 pc/pack					●					






● : Available

■ 6. Protect sheet

Item	Model No.	Discription	Package	Supported product									
				Grit rolling type				Flatbed type					
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000	
	PM-CR-002	Protecting the writing panel from scratches, using for FCX4000-50ES	1 pc/pack										●
	PM-CR-003	Protecting the writing panel from scratches, using for FCX4000-60ES	1 pc/pack										●
	PM-CR-004	Protecting the writing panel from scratches, using for FCX2000-120ES Transparent vinyl, thickness 0.3 mm, Size: 1,328 mm x 968 mm	1 pc/pack									●	

● : Available




7. Adsorption mat

Item	Model No.	Discription	Package	Supported product										
				Grit rolling type				Flatbed type						
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000		
	CM-0002	Adhesive mat Size 610 mm x 435 mm, 1 mm thick, for creasing	2 sheets/pack							●				
	CM-0003-R1A	Double-side coated roll, size 545 mm x 20 m	1 sheet/pack							●	●	●	●	
	CM-0004	Low tack cling mat, size 610 mm x 645 mm	2 sheets/pack							●	●	●	●	
	CM-0005	Micro suction cling mat, size 610 mm x 645 mm	2 sheets/pack							●	●	●	●	
	PM-CM-001	Cling mat for film based type material, size 660 mm x 488 mm	2 pcs/pack											●
	PM-CM-002	Cling mat for paper based type material, size 660 mm x 488 mm	2 pcs/pack											●
	PM-CM-003	For cutting media without backing paper Supported media size: 330mm x 483mm	1 pc/pack					●						
	CR09300-A3-K	For cutting media without backing paper Supported media size: 297mm x 420mm (*1)	2 pcs/pack	●										

(*1) It is used for CE6000-40 and CE6000-40 PLUS.


● : Available

8. Cross cutter blade

Item	Model No.	Discription	Package	Supported product										
				Grit rolling type				Flatbed type						
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000		
	CT01H	Standard type	1 blade/pack			●	●							
	CT02U	High durability type	1 blade/pack			●	●							
	PM-CC-001	For manual cutting across the media	1 pc/pack					●						





● : Available

■ 9. Pouncing tool

Item	Model No.	Discription	Package	Supported product									
				Grit rolling type				Flatbed type					
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000	
	PPA33-TP12	Steel pin 1.2 mm diameter	1 set / pack			●	●						


● : Available

■ 10. Creasing / Scoring tool

Item	Model No.	Discription	Package	Supported product									
				Grit rolling type				Flatbed type					
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000	
	CP-001	Stick type, for heavy paper	1set/pack							●	●	●	●
	CP-002	Roller type (R0.2 mm), for heavy paper	1set/pack								●	●	
	CP-003	Roller type (R0.6 mm), for cardboard	1set/pack								●	●	
	PM-CT-002	Ball on tip of stick, for curve line on heavy paper	1set/pack								●	●	●



● : Available

■ 11. Loupe

Item	Model No.	Discription	Package	Supported product									
				Grit rolling type				Flatbed type					
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000	
	PM-CT-001	Checking blade length, for PHP33 and PHP35 series	1set/pack	●	●	●	●		●	●	●	●	●


● : Available

■ 12. Water-based fiber-tip pen

Item	Model No.	Discription	Package	Supported product								
				Grit rolling type				Flatbed type				
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000
	KF700-BK	Black	10 pens/pack	●	●	●	●			●	●	●
	KF700-RD	Red	10 pens/pack	●	●	●	●			●	●	●


● : Available

■ 13. Water-based fiber-tip pen holder

Item	Model No.	Discription	Package	Supported product								
				Grit rolling type				Flatbed type				
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000
	PHP31-FIBER		1 set / pack	●	●	●	●			●	●	●


● : Available

■ 14. Oil-based ballpoint pen

Item	Model No.	Discription	Package	Supported product								
				Grit rolling type				Flatbed type				
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000
	KB700-BK	Black	10 pens/pack	●	●	●	●			●	●	●


● : Available

■ 15. Oil-based ballpoint pen holder

Item	Model No.	Discription	Package	Supported product								
				Grit rolling type				Flatbed type				
				CE5000	CE6000Plu	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000
	PHP34-BALL	Pen holder for the KB700-BK	1set/pack	●	●	●	●			●	●	●

● : Available

■ 16. Pen adapter

Item	Model No.	Discription	Package	Supported product								
				Grit rolling type				Flatbed type				
				CE5000	CE6000Plus	FC8000	FC8600	CE LITE-50	FC4500	FC2250	FCX2000	FCX4000
	PM-BH-001	For using a commercially available fiber-tip or ballpoint pen	1 pc/pack					●				

● : Available

*: Model numbers are switched to the new ones as soon as the stocks with the old model numbers run out.

*: Availability of items could very depending on the regions.

- Due to the possibility of equipment or PC failure, the data files on the instrument are not guaranteed to hold memory. Please make a backup of data whenever possible to avoid data loss.
- Brand names and product names listed in this brochure are the trademarks or registered trademarks of their respective owners.
- Items mentioned are subject to change without notice. For more information about product, please check the web site or contact your local representative.



For using equipment in correctly and safely

- Before using it, please read the user manual and then please use it properly in accordance with the description.
- To avoid an occurrence of malfunction or an electric shock by leakage, please ensure ground connection and use it in specified power source.

GRAPHTEC
Graphtec Corporation

503-10 Shinano-cho, Totsuka-ku, Yokohama 244-8503, Japan
Tel : +81-45-825-6250 Fax : +81-45-825-6396
Email : webinfo@graphtec.co.jp

Website <http://www.graphteccorp.com>



SUPPLY_SE10405_5D