EasyRoute CNC Router SKU Scheme

Pango		Size	Gantry	Motor	Table	Heads Extra		Spindle			^	Package
Range		3126	Optional	Optional	Table	Optional	Optional	Spinale			Optional	
R		1325	(omitted)	(omitted)	C	(omitted)	(omitted)		30			L
Normal Range		1300 x 2500	Standard 300mm 380V	Stepper	Aluminium T-Slot Clamping	Single Head Standard Machine	No Extra		3kW 220V Spindle			Only Router Itself
R2		2030	L2	S	K	2	D		30	40	50	(omitted)
Heavy Duty Range (Size not 50mm+)		2050 x 3050	Lite 200mm 220V	Servo Motors (need 380V)	PVC Vacuum with Clamp (Cheaper)	Install One Additional Head	Install 5+4 Drilling Head		3kW 4kW 5kW 380V 100mm Spindle			Full Package Include:
Not available on Lite Gantry (L , L2)		2040	L	Omitted when spindle is	V	3			45	55	65	Dust Collector for C/K/V
Except Lite Gantry, all other models with rotary attachment port – to replace X-axis and machine cylinder object. Most options are fixed and only available with new machine manufactured in China.		2050 x 4000 New Router range are carefully design for SA market with extend gantry to cope with 2050mm wide Perspex	Lite 200mm 380V	9kW/12kW ATC Spindle (90 / 120)	Bakelite Vacuum with Clamp (More accurate)	Install Two Additional Head Only 2030/2040 able to install total 3 heads	Not available with Lite Gantry (L/L2) Not available with Water Table (W)	1	4.5kW 5.5kW 6.5kW 380V 125mm High Torque Spindle			Table Vacuum Pump for K/V Table
			Z4		W				75			V
			Raised 400mm 380V, for Supawood Only		Water-Cooling Water table only have Standard 300mm Gantry				7.5kW 380V 125mm High Torque Low RPM Spindle			Only for K/V Table With Vacuum Pump
			Z 6			Additional Head Not available with Lite Gantry (L/L2)						
			Raised 600mm 380V, for Foam Only						(Specially for Aluminium)			
Only Spindle Option,			Z8			Not available			90	1	20	
between can be changed locally.			Raised 800mm 380V, for Foam Only			with Water Table (W)			Auto	12kW matic T ge Spir		