



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China

Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

BT-8032 Anti Migration Base Paste

Characteristic:

Appearance: Dark blue paste

Viscosity: 170000-200000cps

PH value: 8.0-8.5

Odor: mild odor

Solid content: 55%±1

Solubility: soluble in water

Packing specification: 30kg/ bucket

Advantages: Excellent anti-migration effect, excellent washing fastness, soft.

Applicable fabrics: blending cotton fabric, chemical fabric and sublimated fabric etc.

Eco-friendly standards:

1. The formaldehyde, AZO, APEO, phthalates, heavy metals and organotin compounds meet the requirements of Oeko-Tex® Standard 100, GOTS and ZDHC level 3.
2. Comply with the REACH regulations for substances of very high concern.

Printing parameters:

Mesh: 100-120 mesh

scraper: /

Whether to add auxiliary: /

Cleaning: water

Health and Safety: refer to MSDS

Operation process:

Option 1:

A: Firstly Mix 20% rubber paste with 80% anti migration base paste to print as base 2-3 times (The number of prints according to the migrated degree of the fabric);

B: Then print rubber paste clear 1 time ;

C: Finally print the rubber paste on the top.

Option 2:

A: Firstly print rubber paste clear 1-2 times as base;

B: Next Mix 20% rubber paste with 80% anti migration base paste to print 2-3 times (The number of prints according to the migrated degree of the fabric);

C: Then Print rubber paste clear 1 time;

D: Finally print the rubber paste on the top.



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China
Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

Performance test:

1. 60℃ *6 times washing by machine will not fall off the paste.
2. Heat press at 180 degrees for 3-5 minutes will not migrate.
3. 72℃ drying for 72 hours by drying machine(keep humid air);

Attention:

1. Storage period: It can be stored for half a year, the warehouse should keep cool, dry and ventilated.
2. The inside bag should be fastened after use, in case of exposing to the air causing crust.
3. In view of the particularity of anti-sublimation base paste, please ensure the cleanliness of the tool when taking the paste, after opening the bag for use, the inner bag must be emptied with air and re-tightened, and the unused paste cannot be reloaded into the barrel to prevent the introduction of bacteria, so as to avoid mildew and agglomeration.

Tips:

Our company's product information only serve as a test reference data, users need to do sample testing according to your actual production, batch production after confirm qualified.

Fabric printing effect:

