



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China
Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

H-93B Metallic silver paste

Characteristic:

Appearance: Silver paste

Viscosity: 40000-50000 cps

PH value: 8.0 ± 1

Odor: Mild odor

Solid content: /

Solubility: Soluble in water

Packing specification: 20kg/ bucket

Advantages: Excellent shine, no scratching, hand feel soft, Strong metal sense.

Applicable fabrics: Lycra, cotton, knitted fabric, jersey, terry cloth, pull frame cloth, etc.

Eco-friendly standards:

1. The formaldehyde, AZO, APEO, phthalates, heavy metals and organotin compounds meet the requirements of Oeko-Tex® Standard 100, GOTS and ZDHC level 3.
2. Comply with the REACH regulations for substances of very high concern.

Printing parameters:

Mesh: 100-120 mesh

Scraper: /

Whether to add auxiliary: add 1%

Cleaning: water

Health and Safety: refer to MSDS

Printed prescription (depending on the actual situation):

Formula	Toning silver paste	Color pigment
Light color	100%	3-6%
Deep color	100%	To 6%

Operation process:

Step 1: Mix the toning silver paste and color pigment according to the formula in the chart above.

Step 2: Directly print mixed paste onto fabric 2-3 times, or print clear rubber paste 2-3 times as base first, and then print mixed paste on the top 2-3 times (1% fixer could be added to avoid layering).

Performance test: 60°C washing 6 hours by machine will not fall off the powder.



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming
District, Foshan City, Guangdong, China
Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

Attention:

- 1.Storage period: It can be stored for more than one year, the warehouse should keep cool, dry and ventilated;
- 2.The inside bag should be fastened after use, in case of exposing to the air causing crust.

Tips:

Our company's product information only serve as a test reference data, users need to do sample testing according to your actual production, batch production after confirm qualified.

Printing fabric effect:

