



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China
Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

HL-370 Soft Rubber Paste white HL-371 Soft Rubber Paste clear

Characteristic:

Appearance: White paste, light yellow paste

Viscosity: 130000- 170000 cps

PH value: 8.0 ± 1

Odor: Mild odor

Solid content: /

Solubility: Soluble in water

Packing specification: 20&25kg/ bucket

Advantages: Excellent fastness, high coverage, super soft, soft hand feeling.

Applicable fabrics: Cotton, blending and polyester cotton fabric, suitable for oval machine, and flat machine etc. printing.

Eco-friendly standards:

1. The formaldehyde, AZO, APEO, phthalates, heavy metals and organotin compounds meet the requirements of Oeko-Tex® Standard 100, GOTS and ZDHC level 3.
2. Comply with the REACH regulations for substances of very high concern.

Printing parameters:

Mesh: 100-120 mesh

scraper: /

Whether to add auxiliary: /

Cleaning: water

Health and Safety: refer to MSDS

Printed prescription (depending on the actual situation):

Formula	White paste (HL-370)	Clear paste(HL-371)	Color pigment
White color	80-90%	10-20%	/
Medium color	30-50%	50-70%	3-5%
Dark color	0-20%	80-100%	3-5%

Operation process:

1. Mix the white paste, clear paste and color pigment according to the formula in the chart above to print onto fabric 2-3 times.
2. The printed fabric could be naturally dried for 24 hours or baking for 2-3 minutes under the temperature of 130-150°C.



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China
Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

Performance test:

1. For polyester cotton fabric, it's better to add some fixer when printing, which can increase the fastness.
2. 40°C washing 6 hours by machine will not fall off the paste.

Attention:

1. Storage period: It can be stored for more than one year, the warehouse should keep cool, dry and ventilated;
2. The inside bag should be fastened after use, in case of exposing to the air causing crust.

Tips:

Our company's product information only serve as a test reference data, users need to do sample testing according to your actual production, batch production after confirm qualified.

Fabric printing effect:

