



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China
Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

NLF Nylon Rubber Paste White

NLF Nylon Rubber Paste Clear

Characteristic:

Appearance: White paste, light yellow paste

Viscosity: 110000-140000 cps

PH value: 8.0 ± 1

Odor: Mild odor

Solid content: /

Solubility: Soluble in water

Packing specification: 20&25kg/ bucket

Advantages: Excellent fastness, fine and smooth, strong adhesion, not sticky.

Applicable fabrics: water-proof nylon fabric, umbrella cloth and silicone coating fabric etc.

Eco-friendly standards:

1. The formaldehyde, AZO, APEO, phthalates, heavy metals and organotin compounds meet the requirements of Oeko-Tex® Standard 100, GOTS and ZDHC level 3.
2. Comply with the REACH regulations for substances of very high concern.

Printing parameters:

Mesh: 100-120 mesh

scraper: /

Whether to add auxiliary: add 2% fixer

Cleaning: water

Health and Safety: refer to MSDS

Printed prescription (depending on the actual situation):

Formula	White paste	Clear paste	Color pigment
White color	80-90%	10-20%	/
Medium color	30-50%	50-70%	3-5%
Dark color	0-20%	80-100%	3-5%

Operation process:

1. Refer to the formula in the chart above to mix the white paste, clear paste (and pigment), and then print the mixed paste (suggest add 2% fixer to the mixed paste) onto fabric 2 times, each time 2-3 scrapes.
2. If baking, should bake the printed fabric for 3-5 minutes at 100 °C -130 °C, according to the fabric to adjust the temperature and time.
3. After printing 24 hours can do washing testing.



FOSHAN BATU NEW MATERIAL CO.,LTD

Address: A2 Building, No. 576, Industrial Avenue, Genghe Town, Gaoming District, Foshan City, Guangdong, China

Tel: +86 (757)-88898995/6 Web: www.dgbatu.com

Performance test: 60°C washing 1h*4 times by machine will not fall off the paste.

Attention:

1. It is better use up the paste within 2 hours after adding the auxiliaries, otherwise will affect the fastness;
2. Store period: It can be stored more than one year, the warehouse should keep cool, dry and ventilated.
3. The inside bag should be fastened after use, in case of exposing to the air causing crust.

Tips:

Our company's product information only serve as a test reference data, users need to do sample testing according to your actual production, batch production after confirm qualified.

Fabric printing effect:

